

## Clear Grounding Cable

ISO 9001:2015 Certified ISO 14001:2015 CERTIFIED



Image not to scale.

### FEATURES

- Superior flexibility ensures ultimate ease of use.
- Clear PVC jacket ensures ability to see copper stranding and identify breaks.
- Jacket meets the operating temperature range and flame retardancy of ASTM F-855 Type III.
- Heavier jacket walls provide extra protection for copper conductor.
- Excellent cold weather properties to -40°C exceeding ASTM F-855.
- Superior maximum operating temperature range up to 105°C exceeding ASTM F-855 Type III.
- Special and packaging are available upon request.
- Standard indent print with custom inkjet print available upon request.

### APPLICATIONS

- Temporary grounding for de-energized overhead electrical lines and de-energized electrical equipment.

### CONSTRUCTION

Highly flexible stranded No. 30 bare copper conductor insulated with a high grade 105°C clear PVC jacket.

PART NUMBER	GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/1000 FT.
			in	mm	in	mm		
1/0-01GROUNDING-CLEAR	1/0	19/56/.010	0.127	3.23	0.650	16.51	500 or 1000	445
2/0-01GROUNDING-CLEAR	2/0	19/70/.010	0.127	3.23	0.700	17.78	500 or 1000	545
4/0-01GROUNDING-CLEAR	4/0	19/111/.010	0.142	3.61	0.850	21.59	500 or 1000	839

Made in USA

